


Practical Airframe Fatigue and Damage Tolerance



L. J. Bent

PLEASE USE THE **CONTACT FORM** ON

www.sigmak.ltd.uk/contact.asp

TO CHECK AVAILABILITY AND PRICING OF THIS BOOK, or **EMAIL**

lesbent@sigmak.ltd.uk

or **TELEPHONE**

UK (+44) 1292 571 345

PLEASE SEE

www.sigmak.ltd.uk/specialist_training_services.asp

FOR DETAILS OF **FATIGUE AND DAMAGE TOLERANCE TRAINING COURSES** THAT
ARE OFFERED

Practical Airframe Fatigue and Damage Tolerance – the course

“Fantastic course – the perfect balance of problems to teaching. The problems at the end really brought it all together. Your thorough knowledge of the subject really showed. Thanks for passing it on.”

Fiona Scolley, Lead Stress Engineer, Assystem UK Ltd (November 2010)

“An extremely good course – very practical.”

Dave Carter, Stress Engineer, Assystem UK Ltd (November 2010)

“The course covers the fundamentals with detailed illustrations and examples which help to create a solid base to understand the various aspects of crack growth and specific details more easily. I am specifically happy with the simple and easy to understand explanations to various questions raised during the course.”

Sachin Kumaz Rostogi, Stress Engineer, Goodrich IDC (April 2011)

“Training instructor has good practical knowledge and experience.”

Vimal Kumar Jaiswal, Stress Engineer, Goodrich IDC (April 2011)

“Personally the course has been very good to consolidate my understanding and experience. I have learnt hand checks and a feel for things which were missing in my bag. Many thanks for a good course.”

Yogish B. E., Aerospace Engineer, Atkins Aerospace Bangalore (April 2011)

“Overall very good and very well presented.”

Scott Ferry, Consultant Engineer, Airframe Designs Ltd (May 2011)

“Excellent hand-outs and worked examples.”

Andrew Somers, Stress Engineer, Atkins Aerospace Glasgow (May 2011)

“F&DT is a difficult subject to pitch right. Les has done this extremely well.”

Rob Smith, Lead Stress Engineer, Spirit AeroSystems (May 2011)

“Good knowledge of subject well communicated.”

Andrew Thomas, Lead Stress Engineer, Spirit AeroSystems (May 2011)

Practical Airframe Fatigue and Damage Tolerance – the book

“I have to say I'm very impressed. This should be standard reading for any young engineer like myself ... I'm pleased to see it is full of clear explanations and the calculations are used to provide supporting evidence and reference information. Your service has been excellent and I appreciate it very much”

Tyrel Beede, Irvine, California

See also <http://mechanicalhacks.wordpress.com/2011/03/01/bearing-loads-cosine-and-gencoz-distributions/>



t: 01292 571 345

e: lesbent@sigmak.ltd.uk

www.sigmak.ltd.uk

**Fracture mechanics in complex
geometry/stress fields using boundary
element and finite element analysis.**

PRACTICAL AIRFRAME FATIGUE AND DAMAGE TOLERANCE

by

Les Bent

Illustrations by Derek Paul

Published by Sigma K Ltd

Coylton, Scotland

<http://www.sigmak.ltd.uk>

Printed and bound by Antony Rowe Ltd, Eastbourne

ISBN 978-0-9565174-0-1

All rights reserved

Copyright © Sigma K Ltd 2010

No part of the material protected by this copyright notice may be reproduced or utilised or transmitted in any form or by any means, electronic or mechanical, including photocopying, recording or by any information storage and retrieval system without prior written permission from the copyright owner.

Chapter 1. FATIGUE AND DAMAGE TOLERANCE

- 1.1 Fatigue of aircraft structures 1
- 1.2 The rise and fall of safe life and fail safe 2
- 1.3 Damage tolerance 6
- 1.4 Damage tolerance certification regulations 7
- 1.5 Damage tolerant repairs 9
- 1.6 Widespread fatigue damage 10

Chapter 2. FATIGUE PROCESSES

- 2.1 Fatigue crack initiation 13
- 2.2 Effect of stress concentrations on fatigue crack initiation 19
- 2.3 Fatigue crack propagation 22
- 2.4 Fractography 22

Chapter 3. FATIGUE CALCULATIONS

- 3.1 Fatigue cycle definitions 25
- 3.2 SN curves and master diagrams 27
- 3.3 Power law factors 28
- 3.4 Form of SN data – equations or tabular 30
- 3.5 Effect of tensile strength amongst alloy class 31
- 3.6 Test data 31
- 3.7 Effect of mean stress on fatigue life 32
- 3.8 Example of a simple fatigue calculation for a constant amplitude cycle 34
- 3.9 Stress spectra and counting 35
- 3.10 Miner's rule 42
- 3.11 Scatter factors 44
- 3.12 Fatigue calculation programs 45
- 3.13 Strain life fatigue calculations 47
- 3.14 Some statistical aspects of fatigue 49

Chapter 4. FATIGUE OF JOINTS

- 4.1 Introduction 53
- 4.2 Stress concentration factors in joints 54
- 4.3 Stress concentrations in the bearing mode 57
- 4.4 Stress concentrations in the clamped and mixed modes 61
- 4.5 Secondary bending effects 65
- 4.6 Fretting 67
- 4.7 Failure locations under fatigue 68
- 4.8 Analysis of multiple row fastened joints 69
- 4.9 SN data for multiple row attachment joints 79
- 4.10 Lugs 85
- 4.11 Interference fit 91

- 4.12 Cold working 92
- 4.13 Burr marks and scratches 95
- 4.14 Fatigue of bolts 96
- 4.15 Fatigue of bonded joints 97

Chapter 5. CRACKS UNDER STRESS

- 5.1 Fracture mechanics 102
- 5.2 Historical development 103
- 5.3 The effect of a crack in a stress field 107
- 5.4 Crack tip stress intensity factor 111
- 5.5 Fracture toughness 111
- 5.6 Crack growth 114
- 5.7 Crack growth programs 117
- 5.8 Threshold, closure and short crack behaviour 123
- 5.9 Crack growth retardation 127

Chapter 6. STRESS INTENSITY FACTORS

- 6.1 Centre cracked panel 130
- 6.2 Edge crack 132
- 6.3 Surface flaws 134
- 6.4 Small cracks at holes 136
- 6.5 Through cracks at holes 146
- 6.6 Stress gradients 147
- 6.7 Thickness changes 153
- 6.8 Crack tip bulging in fuselages 154
- 6.9 Compounding methods 160
- 6.10 Cracks in stiffened panels 165
- 6.11 Development of crack shape 178
- 6.12 Finite element and boundary element methods 179
- 6.13 Multiple site damage 179

Chapter 7. RESIDUAL STRENGTH

- 7.1 Nett section yield 181
- 7.2 Critical fracture toughness 185
- 7.3 Plastic zone size 186
- 7.4 R-curves 189
- 7.5 Residual strength of stiffened panels 196

Chapter 8. LOAD AND SPECTRUM DERIVATION

- 8.1 Loading spectra 200
- 8.2 Cumulative frequency (exceedence) diagrams 202

- 8.3 Flight profiles 208
- 8.4 Gust and manoeuvre spectra 210
- 8.5 Ground spectra 225
- 8.6 Fatigue calculation using a cumulative frequency diagram 229
- 8.7 Fatigue calculation using a defined time sequence 236
- 8.8 Undercarriage loading 238
- 8.9 Omission of load levels during testing 239
- 8.10 Standard loading spectra 240

Chapter 9. DAMAGE DEFINITION AND INSPECTION

- 9.1 Identification of Principal Structural Elements and Structurally Significant Items 241
- 9.2 Fatigue stresses and damage mapping 242
- 9.3 Static stress levels 244
- 9.4 Geometry and stress concentrations 245
- 9.5 In-service data 248
- 9.6 Test data 249
- 9.7 Material properties 250
- 9.8 Areas prone to accidental damage 250
- 9.9 Initial damage assumptions 250
- 9.10 Detectable damage pre- and post-MSG3 252
- 9.11 Non-destructive testing (NDT) 258
- 9.12 The non-destructive testing manual 260
- 9.13 Eddy current testing (ET) 260
- 9.14 Magnetic testing (MT)/Magnetic Particle Inspection (MPI) 261
- 9.15 Penetrant testing (PT)/Penetrant Flaw Detection (PFD) 262
- 9.16 Radiographic testing (RT) 262
- 9.17 Ultrasonic testing (UT) 263
- 9.18 The interface between the Stress Office and NDT 264

Chapter 10. CERTIFICATION CALCULATIONS

- 10.1 Overview of calculation process 265
- 10.2 Report layout 271
- 10.3 Assemble background data 271
- 10.4 Load path, expected damage progression and detectable damage 272
- 10.5 Limit load and test/in-service factors 272
- 10.6 Fatigue loads 272
- 10.7 Stress intensity factor calculation 273
- 10.8 Critical crack length 273
- 10.9 Threshold calculation 273
- 10.10 Repeat inspection period calculation 274
- 10.11 Single load path structure 277
- 10.12 Multiple load path structure CASE 1: SD item intact until PD item failure 278
- 10.13 Multiple load path structure CASE 2: PD item fails before SD item 280

- 10.14 Multiple load path structure CASE 3: SD item fails before PD item 282
- 10.15 Reporting and summary sheets 284
- 10.16 General considerations 284

Chapter 11. DAMAGE TOLERANCE OF TYPICAL STRUCTURE

- 11.1 Lugs 287
- 11.2 Spanwise/chordwise wing joints 303
- 11.3 Spar joints 313
- 11.4 Fuselage lap/butt joints 317
- 11.5 Fittings 321
- 11.6 Stiffened panels 323
- 11.7 Wing/empennage cut outs and holes 332
- 11.8 Spars 335
- 11.9 Fuselage cut-outs and holes 341
- 11.10 Stringer run outs 345
- 11.11 Ribs 347
- 11.12 Fuselage pressure bulkheads 349

Chapter 12. DAMAGE TOLERANCE OF REPAIRS

- 12.1 Introduction 352
- 12.2 AC 120-93 and the three stage repair approval process 353
- 12.3 Considerations before metal is cut 355
- 12.4 Stop drilling 358
- 12.5 Use and abuse of power laws 361
- 12.6 Oversizing and bushing holes 365
- 12.7 Oversizing and spotfacing holes 372
- 12.8 Cold working of holes 374
- 12.9 Blend repairs to skin and flange elements 375
- 12.10 Repair doublers 380
- 12.11 Inspection requirements 387
- 12.12 Repair doubler proximity 390
- 12.13 Widespread fatigue damage and repair doublers 393
- 12.14 Availability of data 393

REFERENCES 401

SUBJECT INDEX 409

Practical Airframe Fatigue and Damage Tolerance

Index

Note: Figures are indicated (in this index) by *italic page numbers*, Tables by **emboldened numbers**, and footnotes by suffix 'n'. Abbreviations used in index: PD = primary damage; SD = secondary damage; SIF = stress intensity factor; SSI = structurally significant item

- 1 g on the ground (1GOG) stress 210
 2024-T3 material 35, 43, 80, 189
 2024-T4 material 358
 2024-T351 material 291
- AC 120-93 repair approval process 353–5
 access rating [in detectable crack calculations] 257
 accidental damage, areas prone to 250, 290
 adhesively bonded joints *see* bonded joints
 adhesives
 high-temperature curing compared with cold bonding 65
 and stress concentrations at knife edged fastener holes 64–5, 317
- AFGROW
 material data 291
 output file for example 298
 SIF solution 295, 296
- Ageing Aircraft Working Group (AAWG), Final Report 12, 51
- Air Transport Association (ATA), guidance document on NDT instruction 259
- Airbus UK 286
 aircraft maintenance planning, updates 354
 aircraft mass ratio 212
 Aloha B737 accident 10, 12, 65, 317
 alternating stress 26
 relationship to proof stress 31
 AMC 20-20 10, 353
 angularity [between bolt head and retaining nut] 96, 97
 arrest of crack 196–7, 326, 327
 Avro 688 Tudor 2, 3
 axial scratches, fatigue life affected by 95
- BAe ATP wing and fuselage 248
 BAe Jetstream 9
 BAE SYSTEMS
 formation of 286
 P621 computer program 235
 banked turn manoeuvre 212–13
 basic detectable crack length 255
 factors affecting 256–7
 Basquin exponent/relationship 29, 48, 49
 beachmarks 23
 bearing mode of load transfer
 and clamping mode 62–4
 effect of load transfer on fatigue life 58, 59
 stress concentrations in 56, 57–61
 bearing stress
 in joints 57, 384, 385
 in lugs 295, 302
 bending stress distribution, in spar 339
 beta (β) 111
 centre cracks 130–1, 193
 corner cracks at holes 136, 138
 edge cracks 133
 surface flaws 134
 biaxial loading, at crack tip 108
 blend repairs 375–80
 reinforcement for 378, 380–1
 blunting of crack 325
 body-centred cubic (bcc) crystal structure 13, 14
 Boeing 707 4, 5, 5, 6
 Boeing 737 10, 65
 Boeing fastener flexibility formula 71, 72
 Boeing fatigue methods 244
 bolt bending 96, 379
 bolted joints 62
 bolts
 ‘cocking’ of 96, 97
 fatigue of 96
 bonded butt joints, fatigue of 100, 101
 bonded joints
 debonding and failure of 10, 65, 317
 fatigue of 97–101
 load–extension curve 175
 bonded lap joints, fatigue of 100, 100
 boundaries 160, 246
 boundary element method, SIFs determined using 179
 Bowie factor 136, 137, 368, 369
 braking loads 238
 break out of cracks 308–9, 312 & n, 322
 break through of cracks 309
 British Aerospace plc 286
 see also BAE SYSTEMS
 brittle fracture 110, 112
 bulging factors 154–7
 comparison of various factors 157, 158–9
 burr marks, fatigue life affected by 95
 bushing of oversized hole 356, 365–72

- butt joints 53, 54
 - fatigue of 100, 101
- butt strap 306, 307
- castellations in ribs 347–9
- centre crack in panel
 - offset crack 146, 308
 - SIF for 130–2, 193, 194
- certification calculations
 - background data for 271–2
 - critical crack size calculations 273
 - fatigue loads 272–3
 - general considerations 284–5
 - hand calculations for checking 285
 - inspection threshold calculations 273–4
 - limit loads defined 272
 - load path type defined 272
 - material data for 272
 - multiple load path structure 267–70
 - overview of process 265–70
 - repeat inspection interval calculations 274–83
 - report compilation 284
 - report layout 271
 - re-run after repairs 395
 - SIF calculations 273
 - single load path structure 265–7
 - summary sheet(s) for 284
- certification specifications 7–8
- chordwise wing joints 303–4, 307
 - see also* spanwise/chordwise wing joints
- Civil Aviation Authority, documents on NDT processes 259
- clamping force 61
- clamping mode of load transfer
 - and bearing mode 62–4
 - stress concentrations in 56, 61–2
- clearance fit, effect on fatigue life 82, 83, 384
- clearance fit fastener, load distribution through 371
- clevis arms
 - failure of primary arm 290, 290, 291
 - rogue flaws in 287, 288, 295
- clipping of fatigue test spectrum 128, 239
- close-packed directions 15
- close-packed planes 14–15
- cloud warning radar, and gust frequency data 214, 214, 215, 216
- Code of Federal Regulations, Title 14 (14 CFR)
 - Part 25 Transport Category Aeroplanes
 - Amendment 45 7, 9
 - Amendment 96 7, 9
- cold-bonded doubler, failure of 10
- cold expansion process 92, 360, 374
- cold working of holes 92–4, 374–5
 - effect on fatigue life 82, 83, 92–4, 360
 - stop drill holes 360–1
- Comet 3–4, 4
- compounding method 160–5
 - applied to stiffened panels 175–6
 - for crack crossing boundary 162, 164–5
 - for crack near free edge and hole 161–2, 162
 - for through cracks at holes 146, 160
- condition rating [in detectable crack calculations] 257
- confidence interval 51
- congestion rating [in detectable crack calculations] 256
- connected structure, spectrum at 398
- constant-amplitude cycle 25, 26
 - example of fatigue calculation 34–5
 - ‘mapped’ onto crack growth curve 396, 397
- constant-life diagrams 32, 33
- contour flying, gust data 214
- corner cracks 136, 147, 182
 - break out as through cracks 308–9
 - detectable sizes 261, 264, 297, 298
- corner flaws at holes, SIFs for 136–45
- corrosion
 - inspections for 374
 - material loss due to 260, 263
 - on one side of hole 378–80
 - repairs to deal with 365, 372, 375, 378–80
- cosine distribution, of bearing stress 57, 58
- countersink fasteners, detectable crack lengths at 254
- countersinking 385, 386
 - see also* knife edged countersinks
- counting of cycles 36–42
 - representation of counted spectrum 41
- counting methods
 - effect on crack growth curves 41, 42
 - hand calculations 38–9, 40
 - rainflow method 37–9, 40
 - reservoir method 39, 40
- crack arrest 196–7, 326, 327
- crack closure 123–4
- crack growth curves
 - blend repairs 376
 - constant-amplitude cycle ‘mapped’ onto 396, 397
 - fittings 322
 - fuselage lap joints 319, 320
 - lugs 298, 302 & n, 303
 - open hole in wing/empennage 333, 334
 - oversized hole 356, 357

- crack growth curves (continued)
 - PD item
 - with SD item failed 275, 276, 283
 - with SD item intact 275, 276, 277, 279, 281, 283
 - post-repair curve 396, 397
 - ribs 349
 - SD item
 - with PD item failed 275, 276, 281
 - with PD item intact 275, 276, 279, 281, 283
 - spar joints 314, 316
 - stiffened panels 327, 328, 329, 331, 331
 - stringers 310, 312
 - in summary sheets 284
 - wing joints 310, 312
- crack growth programs 117–23
 - direct integration example 121–3
 - Mathcad program 118–19, 120, 122, 123
 - tabular calculation example 120–1
- crack growth rate vs SIF range curve 114, 361
- crack growth resistance curve 190
 - see also* R-curve
- crack growth retardation 127–9
 - use in crack growth methods 118, 128
- crack growth threshold 114, 115, 123, 274, 355
- crack length, detectable 253, 255
- crack path, factors affecting 246–7
- crack shape, development of 178–9
- crack-stopping elements 265–6
- crack in stress field
 - effects caused by 107–10
 - polar coordinate system 107
- crack tip
 - biaxial loading at 108
 - through-thickness constraint at 108
- crack tip blunting 325
- crack tip plastic zone 123–4, 186, 301
- crack tip plastic zone size
 - in crack growth calculations 119, 120
 - in residual strength calculations 184, 186–9
- crack tip stress intensity factor 111
 - calculation for lug example 299, 300
 - crack shape development using 178–9
 - effect of fuselage radius of curvature 154
- cracks, hidden and visible parts 253, 254, 255
- cracks in stiffened panels 165–77
- cracks under stress 102–29
- critical crack driving force 106, 111
- critical crack length 181
 - determination of 105, 195, 196, 273, 299
- critical fracture toughness 185–6
- critical stress intensity factor 111
- critically resolved shear stress
 - notation 15
 - for slip 16
- cumulative frequency diagram(s) 200, 202–7
 - calculation from frequency spectrum 203–4
 - fatigue calculations using 229–35
 - fatigue spectrum calculated from 206–7
 - gust and manoeuvre spectrum plotted as 225
 - see also* exceedence diagrams
- cut outs
 - crack initiation and growth at 150, 245–6
 - crack path affected by 246, 247
 - in fuselage 341–5
 - as repair method 378, 380, 381–7, 392
 - stress differences between inner and outer skins 4
 - in wing and empennage structure 332
- cycle counting 36–42
 - see also* counting methods
- cycle-by-cycle crack growth calculations 118, 128
- dagger bracket 305, 306
- damage definition and inspection 241–64
- damage mapping 243
- damage progression
 - in calculations 272, 285
 - at open holes 334
 - spar flange 338
 - in spar flange strap 315
 - in stiffener 329
 - in stringer 312
 - in wing skin 337
- damage ratio (Miner's rule calculation) 44
- damage tolerance 6–7
 - application to repairs 9–10, 352–400
 - certification regulations 7–9, 274
- damage tolerance analysis *see* fatigue and damage tolerance analysis
- damage tolerance evaluation (DTE) 353
 - assumed initial damages 7, 250–1
 - objective 7–8
- Damage Tolerance Inspections (DTIs) 353, 354
- damage tolerant design 274
- de Havilland Comet 3–4, 4
- defined time sequence, fatigue calculations using 236–8
- de-pressurisation 342

- design service goal (DSG), and fatigue test 9, 249, 317
- detailed visual (DV) inspection 252, 253, 292
- detailed visual inspection (DET) 255
- detectable crack sizes, for various NDT methods 260, 261, 262, 263, 264, 297
- detectable damage 252–8, 272
 - MSG-3 analysis 254–8
- detection of cracks
 - NDT methods 258–64
 - visual methods 252–8
- deterministic cycle 35, 36
 - identification of 37
- direct integration method 118, 121, 122, 372, 377
- discrete stiffener 266–7
- displacement compatibility analysis 69–79
 - re-run after failure of fasteners or stiffeners 198
- domed pressure bulkheads 350
- door cut outs, fatigue and damage tolerance analysis 342–4
- Dornier Merkur 1, 2
- double butt joints 53, 54
- double-notched bar, fatigue life, size effect 21
- double scarf joint 77
- double shear joint 77
- doublers
 - failure of 10
 - load path through 176, 342
 - see also* repair doublers
- Douglas DC-6 3
- Douglas DC-8 4–5
- Douglas DC-10, fuselage bulging factors used 156, 159
- down-gusts
 - cumulative frequencies 223, 224
 - see also* up-gusts
- ductile materials, crack growth resistance 189
- durability
 - adhesives 65
 - joints 305
 - repairs 384
- early aircraft, fatigue failures 1–2
- EASA
 - certification specification CS25 7, 8
 - guidance on ageing aircraft programmes 353
 - on NDT nominated person 258
- eddy current test method 260–1
 - applications 10, 260–1, 297, 323, 355, 357, 389–90
- edge crack
 - compared with embedded crack 175, 253
 - gaping of 132, 253, 321
 - SIF for 132–5
- edge factor [in detectable crack calculations] 257
- edge margin, in repair doubler 383, 385
- effective crack growth power laws, configurations to determine 363, 364
- effective crack length 176, 194, 334, 347
- effective power laws 362–4
 - example calculations 363, 377, 395
- effective stress concentration, lugs 89
- El Haddad short crack correction 125–6
- elastic modulus 272
- elastic–plastic fracture mechanics 102
- elliptical stress concentration, crack treated as 103
- embedded crack, compared with edge crack 175, 253
- embedded flaw, nett section stress calculation 182
- empennage, principal structural elements listed 242
- empennage cut outs and holes, fatigue and damage tolerance analysis 332–4
- ended stiffener 346–7
 - modelled as effective crack 347
- endurance
 - determination for constant-amplitude cycle 35
 - effect of mean stress 32–4
 - see also* fatigue life
- equivalent axial load (EAL), lugs 89–90
- equivalent initial flaw size 251
- ESDU data series
 - accelerometer data 213, 225
 - S–N* curves 30
- exceedence diagrams 200, 202–7
 - blocking off [into steps] 206, 237
 - for civil aircraft 204
 - derivation for separate flight stages 127, 216–18
 - fatigue spectrum calculated from 206–7
 - for flight over mountainous terrain 205
 - for military aircraft 204
- external surveillance 252
- extrusions 16, 17, 18
- F-111 aircraft 6
- FAA
 - Advisory Circular AC 120-93 9, 353–5
 - certification by 7, 9
 - failures of 10

- face-centred cubic (fcc) crystal structure 13, 14
 - close-packed planes in 14–15
- 'fail safe' design philosophy 5–6
- failure mode
 - of bolts 96
 - of bonded joints 65, 100–1, 317
- FALSTAFF loading spectrum 240
- fast fracture 17, 189, 326
- fastener diameter, in repair doublers 384
- fastener failure 198, 199
- fastener flexibility 71, 272
 - Boeing formula 71, 72
 - effect on load transfer 74–5
 - effect on SIF 169, 170
 - factors influencing 71
 - Grumman formula 71, 72
 - Huth's formula 71, 72
 - Swift's formula 71, 72
- fastener holes, crack initiation and growth at 245
- fastener pitch, SIF affected by 168, 169
- fastener rows, bonded joints 98
- fastener types
 - high-quality types 82, 84
 - load–displacement curves 170–3
 - repair durability affected by 384–5
 - SN curves 82, 83
- fatigue analysis, wing/empennage cut outs and holes 332–3
- fatigue calculation programs 45–7
- fatigue calculations 25–52
 - cumulative frequency diagrams used 229–35
 - defined time sequence used in 236–8
 - at design stage 244
 - safety factors applied to 18–19
 - statistical aspects 49–52
- fatigue crack growth 22, 114–17
 - effect of overloads 128
 - see also* crack growth
- fatigue crack growth programs 117–23
- fatigue crack initiation 15–19
 - effect of stress concentrations 19–21, 245–6
 - and fretting of joint 68
- Fatigue Critical Baseline Structure (FCBS) 353
- fatigue cycle, definitions 25–7
- fatigue and damage tolerance analysis
 - application to repairs 352–400
 - fittings 321–3
 - fuselage cut outs and holes 341–5
 - fuselage lap/butt joints 317–20
 - fuselage pressure bulkheads 349–51
 - lugs 287–303
 - ribs 347–9
 - spanwise/chordwise wing joints 303–13
 - spar joints 313–16
 - spars 335–41
 - stiffened panels 323–32
 - stringer run outs 345–7
 - wing/empennage cut outs and holes 332–4
- fatigue life
 - effect of mean stress 32–4
 - of joints, factors affecting 53, 54–68
 - relative influence of loading actions **201**
 - size effect 21
 - see also* endurance
- fatigue limit 28, 31
- fatigue spectrum, generation of 206–7, 243, 272–3
- fatigue spectrum program, inputs into 210, 243
- fatigue strength, effect of tensile strength 31
- fatigue strength exponent 29
- fatigue stress
 - and damage mapping 242–3
 - maximum 312, 314, 322, 334, 336, 338
- fatigue test spectrum
 - mixed metal/composite structures 129
 - omission of stress cycles 129
 - truncation of 4, 128, 129
- fatigue testing 31–2
 - Comet aircraft 3–4
 - and design service goal 9, 249
 - safety factors applied to 18–19
 - specimens 31–2
 - test machines used 32
- fatigue threshold 44, 274, 287
- filled hole
 - with stiff material 54, 55, 56
 - with very flexible material 56
- finger doublers 387–8
- finite element method
 - SIFs determined using 179
 - test/in-service factors affecting 272
- finite width corrections 135, 137, 369
- fittings, fatigue and damage tolerance analysis 321–3
- flanges
 - fitting flange 321–3
 - shear and bending loads on 322
 - spar flange 313, 335
- flat plates, as series of stiffening elements 176–7
- flat pressure bulkheads 349–50, 351
- 'fleet proven life' 51–2
- flexibility [fastener load–displacement curve] 170

- flight profiles 208–10, 219
 - checking against fleet utilisation 209–10
 - loading actions considered in 209
 - tabular form **208, 220**
- flush repairs 388, 389
- Forman equation 116
- fractographs, copper single crystal 16, 18
- fractography 22–4
- fracture mechanics 102–3
 - historical development 103–7
 - literature on 102–3
- fracture surface, characteristic features 23–4
- fracture toughness 111–14, 185–6, 272
 - effect of orientation of test specimens 113–14
 - thickness dependence 112–13
- frames, in fuselage structure 318, 342–3
- frequency spectrum 202
- fretting 67–8
- friction [in clamped joint] 56, 61–2, 63
- fuselage
 - crack tip bulging in 154–60
 - principal structural elements listed 242
 - stress stiffening effect 155, 156
- fuselage axial stress 154, 155, 398
- fuselage cut outs and holes, fatigue and damage tolerance analysis 341–5
- fuselage hoop stress 154, 155, 398
- fuselage lap/butt joints
 - fatigue and damage tolerance analysis 317–20
 - load transfer in 77–9
- fuselage pressure bulkheads, fatigue and damage tolerance analysis 349–51
- fuselage pressurisation cycle 3, 26
- fuselage skin panels 77
 - failure of 196, 197, 199
 - joints 53, 54, 77, 303, 306
- GAG cycle 36–7, 127, 229
 - blocking [into steps] 237
 - exceedence diagram 229, 230, 237
- GAG spectrum 229
 - example calculation 230–1, 231, **232**
 - maximum and minimum stress levels derived from 232, 233
- gamma [in Bowie factor] 137
- gauge factor [in detectable crack calculations] 257
- Gaussian distribution *see* normal distribution
- Gencoz distribution, of bearing stress 57, 58
- General Dynamics F-111 6
- general surveillance 252
- general visual inspection (GVI) 255
- geometry effects, fatigue crack growth affected by 19–21, 246–7
- geometry factor 111, 118, 394
- Gerber–Goodman mean stress correction factor 33, 46, 81
- Gerber relationship 33
- Goodman diagrams 32, 33
- Goodman relationship 33
- grain boundary 13
- grain orientation 271
- Green's functions 150, 166
- Griffith's energy balance 105
- ground–air–ground (GAG) cycle 36–7, 127, 229
- ground loading spectrum 225–8
 - combined with gust and manoeuvre spectrum 229, 230
 - for take-off phase **228, 229**
 - see also* taxi loading spectrum
- Grumman fastener flexibility formula 71, 72
- gust alleviation factor 211
- gust encounter, aircraft response to 211–12
- gust frequencies
 - averages data 213–15, 218
 - relative frequency ratio 215, 216, 217, 218
- gust increment 212
- gust loading 200
- gust and manoeuvre spectrum 210–25
 - combined with ground loading spectrum 229, 230
 - data sets used 213–15
 - example of derivation 219–24, 225
 - plotted as cumulative frequency diagram 225
 - procedure for derivation 216–18
 - split into gust and manoeuvre components 204, 205, 207
- hat section stringer 175, 317
- Hawker Siddeley HS 748 6, 248
- heel flaw [in flange] 338
- hemispherical pressure bulkheads 350
- hexagonal close-packed (hcp) crystal structure 13, 14
- Heywood's aluminium lug curve 292, 294
- Heywood's light alloy bolted joint SN curve 46, 81, 83, 243
- Hi-Lok fastener 84
 - fatigue life data 82, 83
 - hole filling factor 384
- Hi-Tigue fastener 82, 84
- hidden cracks 253
- high-frequency eddy current (HFEC) test method 260, 323, 355, 389
- high-load transfer joints 84
 - fatigue life data 82, 83
- hinged-hinged lap joint 66

- hole
 - stress concentration at 20–1, 54–6
 - see also* filled hole; open hole
- hole filling factor 59, 384
- hole interaction factors (HIFs) 82
- Huck Lockbolt 84
- Huth's fastener flexibility formula 71, 72

- impact on landing 36
- in-service data, SSIs identified using 248–9
- infinite life 32 & n
- initial quality flaw sizes 251–2
- inspection interval 8, 252
 - see also* repeat inspection interval
- inspection requirements, repairs 387–90
- inspection standards [MSG-3] 255
- inspection start point (ISP) 12
- inspection threshold 8, 9, 273–4, 302–3, 365, 374
- integral stiffener 175, 266
- integration
 - Mathcad method 118, 121, 122, 364, 368, 395
 - of Paris equation/law 117, 367, 372, 395
 - of SIF 369, 372, 395
- interfays, effect on stress concentration factor at joints 64
- interference fit 91–2
 - effect on fatigue life 32–3, 82, 83, 91–2, 384
- intermediate fracture toughness 112, 185
- intrusions 16, 17, 18

- Jarfall's stress severity factor 59–60
 - see also* stress severity factor
- joints
 - bearing mode 56, 57–61
 - clamping mode 61–2
 - failure locations under fatigue 68–9
 - fretting of 67–8
 - mixed load transfer mode 62–3
 - relative movement in 67–8
 - secondary bending effects in 65–7
 - static strength calculations 244–5
 - stress concentration factors in 54–6
 - types 53–4
 - ways of manipulating load transfer in 75, 76
 - see also* butt joints; lap joints; lug/clevis joints; scarf joints; step joints; three row joints; two row joints;

- K-curves
 - determination in example 193–4
 - tangency with R-curves 191, 192, 195, 196, 197

- knife edged countersinks
 - and structural adhesives 64–5, 317–18
 - see also* countersinking

- landing gear components, strain life approach used 48
- landing impact 36
- lap joints 53, 54
 - double row
 - secondary bending effects in 65–7
 - stress severity factor for 60
 - failure of cold bonding 65, 317
 - fatigue of 100, 100
 - fretting in 67–8
 - fuselage lap joints 317–20
 - single row 60, 385
 - stiffening of 67
- life extension programme, and damage tolerance methods 274
- Life Improvement Factors (LIFs) 374
- ligament
 - failure of 186, 301
 - remaining 188, 301
- lighting rating [in detectable crack calculations] 256
- limit loads 272
- limit stress
 - in critical crack length calculations 193
 - in post-repair calculations 399
 - in residual strength calculations 174, 198, 245
- limit of validity (LoV) 249
- limiting ruling section 272
- linear elastic fracture mechanics (LEFM) 102
- load path 272
 - categories 265–70
- load ratio
 - calculation of 44
 - in S–N curve 26
- load redistribution factors 276
 - stiffened panels 326
 - wing joints 310, 313
- loading, classification of 200
- loading actions, relative influence on fatigue life **201**
- loading spectra 26, 27, 200–1
 - at connected structure 398
 - counting of cycles 36–42
 - presentation forms 202
 - standardised spectra 240, 399
 - see also* ground loading spectrum; gust and manoeuvre spectrum
- local stress scaling, post-repairs 395, 396
- locations, damage development, identification of 242, 243, 244
- Lockbolt fastener 84, 384

- log-mean life 51
- log-normal distribution 50
- low-frequency eddy current (LFEC) test
 - method 389, 390
- low-level flying, gust data 214
- low-load transfer joint 84
 - fatigue life data 82, 83
 - test specimen 85
- lugs 53–4, 85
 - damage tolerant arrangement 288
 - effect of fit of pin 87, 144
 - effect of shape 86, 87, 144
 - effective stress concentration calculation 89
 - fatigue and damage tolerance analysis 287–303
 - example calculation 291–303
 - fatigue life calculations 85–9, 245, 292–3
 - geometry [for two-arm lug] 292
 - initial damage in 294–5
 - inspection methods 292
 - load distribution between 288–9
 - loading spectra 398
 - notation and sign convention 88
 - SIF applied to analysis 144, 295–7
 - size correction factor 88
 - size effect 87–8, 293
 - stress concentration factor variation 88–9, 89, 293–4
 - see also* pin-loaded lugs
- machined steps in joints 76
- magnetic testing 261–2
- Maintenance Steering Group 3 *see* MSG-3
- manoeuvre loadings 200, 212–13
- Manson–Coffin exponent/relationship 48, 49
- mass distribution, in post-repair calculations 399–400
- material properties, SSIs identified by 250
- Mathcad routines
 - crack growth program 118–19, 120, 370
 - fatigue life calculation 45
 - integration 118, 121, 122, 364, 368, 395
- maximum principal stress, crack growth
 - perpendicular to 246, 247, 339
- maximum stress 26
- mean stress 26
 - fatigue life affected by 32–4
- mean stress correction factor (MSCF) 81
- medium load transfer joint 84
 - test specimen 85
- metallic crystal structures, types 13, 14
- microcracks 16, 17, 124
- MIL-HDBK-5
 - S–N* curves 30
 - see also* MMPDS-04
- Miner’s rule 42–3
 - example calculation 43–4
- Mini-TWIST loading spectrum 240
- minimum stress 26
- mixed mode of load transfer 62–3
- modified Sih method 147–8, 394
 - example calculation 149–51
- mountainous terrain, exceedence diagram for
 - flight over 205
- MSG-3 analysis 254–8
 - inspection standards 255
 - process sheet 258
- multiple element damage (MED) 11, 249
- multiple load path, damage tolerant structure 267–70
 - crack growth curves 275, 276
 - repeat inspection interval calculations 275–6, 278–83
- multiple row attachment joints, SN curves for 79–85
- multiple row fastened joints, load transfer analysis 69–79
- multiple site damage (MSD) 11, 249
 - factors affecting crack path 247, 248
 - at fuselage lap joints 317–18, 319
 - SIFs for 179–80
- NASGRO equation 116
- NASGRO material database 189, 291
- NASGRO User Manual 182
- NDT 258–60
 - detection thresholds 259–261, 262, 263, 264, 356, 357, 365, 376
 - methods 260–4
 - and repairs 357–8, 389–90
 - see also* eddy current test method; X-radiography
- NDT Department, interface with Stress Office 264, 389n
- NDT inspection instruction 259
 - feedback on application 259
- nett section yield 17, 181–4
 - applications 299, 327
- Nimrod MRA4 5
- non-destructive testing *see* NDT
- non-destructive testing manuals (NTMs) 259, 260
- normal distribution 49–50
 - cumulative distribution function for 50
- offset hole, flaw at 146
- omission of stress cycles during fatigue
 - testing 129, 239
- once-per-flight stress level 119, 174, 196, 273, 310, 399

- open holes
 - filled with stiff material 54, 55, 56
 - filled with very flexible material 56
 - with pitch circle attachment holes 333
 - stress concentration factors 20, 21, 54, 55, 103, 332–3
 - in wing and empennage structure 332–4
- operational loads measurement (OLM) data, counting methods used 41
- overload, plastic zones formed during 127–8
- overload regions, in fracture surface 23
- oversized hole
 - crack growth curve 356, 357
 - fatigue life calculations 365
- oversizing 86, 94, 356–7
 - and bushing 356, 365–72
 - and spotfacing 372–4
 - upper limit on 371
- overswing factors 225–6
- oxide, in crack opening/closing 123, 124
- pagoda roof [cycle counting] method 37, 38–9
- panel *see* skin panel
- Paris equation/law 114, 117, 393
 - determination of coefficients and exponents 115–16
 - integration of 117, 367, 372, 395
- Paris regime, crack growth rate during 114, 361, 367
- penetrant testing 262
- persistent slip bands 16
- phase change 13
- pin-loaded lugs, stress distribution around 57–8
- pitching moment, in gust encounter 211
- pitting corrosion 376n
- plane strain 110
- plane strain fracture toughness 112, 186, 287
- plane stress 109, 194
- plane stress fracture surface 24, 110
- plane stress fracture toughness 112, 287
- plastic zone [at crack tip] 123–4, 186, 301
- plastic zone size
 - in crack growth calculations 119, 120
 - Irwin's approximation 186
 - in residual strength calculations 186–9
 - steel compared with aluminium 189
- plate element flexibility 70
- Poisson's ratio 109, 272
- power law factors 28–9
- power laws
 - crack shape developed using 179
 - use and abuse of 361–5
- practicality rating [in detectable crack calculations] 257
- pressure bulkheads 349–51
- pressurisation cycle 3, 26
 - and fuselage pressure bulkheads 351
 - and fuselage skin lap/butt joints 317
- pressurised aircraft, early development of 2–4
- primary damage (PD) 250
- primary load path 250
- principal stress, and crack path 246, 247
- principal structural elements (PSEs)
 - evaluation of 7–8
 - identification of 241
 - inspection thresholds for 8
 - typical PSEs listed 242
- principal structural elements (PSEs) loading
 - severity assessed for 242
- probability density distribution, normal [or Gaussian] 49, 50
- programs
 - BAE Systems P621 235
 - crack growth 117–23
 - fatigue life calculation 45–7
- proof strength 272
- proof stress, relationship to alternating stress 31
- R-curves 189–96
 - computational method 192
 - example calculation 193–6
 - graphical method 191, 192
 - prediction of skin-critical failure 192
 - stiffened panel 327
 - tangency with K-curves 191, 192, 195, 196, 197, 326, 327
 - under plane strain conditions 191
 - under plane stress conditions 191
- radiographic testing 262–3, 390
- rainflow [cycle counting] method 37, 38–9
 - counting algorithms 37
 - effect on crack growth curve 41, 42
 - and exceedence diagrams 202
- Ramberg–Osgood equation 48
- ratchet marks 23–4
- regulations 7–9, 274
- relative gust frequency ratio 215, 216, 217, 218
- Repair Assessment Guidelines (RAGs) 353, 354, 393
- repair cut-outs 378, 380, 381–7
 - vertical separation between 392
- repair doublers 380–7
 - disadvantages 378
 - good design practices for 386
 - influences on fatigue and crack growth life 383–6
 - as load carrier for cut outs 380, 381–7

- repair doublers (continued)
 - load paths in 381, 382
 - material used 385–6
 - proximity to other repair doublers 391–2
 - as reinforcement for blend repairs 378, 380–1
 - shape 386
 - and widespread fatigue damage 393
- Repair Evaluation Guidelines (REGs) 353, 354, 393
- repair plates
 - material used 385–6
 - shape 386, 387–8
- repairs
 - AC 120-93 approval process 353–5
 - considerations before metal is cut 355–7
 - data availability for 393–400
 - fatigue and damage tolerance theory
 - applied to 9–10, 352–400
 - inspection requirements 387–90
 - threshold for 354, 355, 387
 - see also* repair doublers
- repeat inspection interval 8, 252, 274–7
 - effect of oversizing 367–70
 - meaning of term 277
- repeat inspection interval calculations
 - for blend repairs 376, 377
 - for fittings 323
 - for fuselage cut outs 344
 - for lugs 302
 - multiple load path structure 278–83
 - PD item failure before SD item failure 280, 281
 - SD item failure before PD item failure 282, 283
 - SD item intact up to PD item failure 278, 279
 - for open holes 334
 - for oversized holes 367–70
 - for repair doublers 386
 - for ribs 349
 - scatter factors used 277, 287, 377
 - single load path structure 277–8
 - for spanwise/chordwise wing joints 312
 - for spar joints 316
 - for spars 340, 341
 - for stiffened panels 330
 - for stringer run outs 347
 - stringer run outs 347
- reservoir [cycle counting] method 39, 40
- residual gust spectrum 229–30
 - example calculation 232–5
 - exceedence diagram 234, 237
- residual strength 181–99
 - of stiffened panels 196–9
- residual strength diagrams 198, 199, 273, 312, 330–1, 330
- retardation of crack growth 127–9
- Rhodes [crack growth rate] equation 116, 118, 120
 - integration 373, 377
- ribs, fatigue and damage tolerance analysis 347–9
- rivet diameter, in repair doublers 384
- rivet pitch 66
 - in repair doublers 384, 385
- rivet squeeze force 384
- riveted joints
 - S N curves 28, 82, 83
 - stress concentration factor calculations 61
- rogue flaws 250, 252
 - in clevis arms 287, 288, 295
- rotating probe eddy current inspection 261, 323, 355, 357, 366
- row spacing, in repair doublers 384
- S N curves 27–8
 - experimental determination 31–2
 - fatigue damage calculated using 42–4, 243
 - inspection threshold determined using 274
 - for lugs 293
 - scatter at various points 28, 29
- S N data
 - forms [equation/tabular] 30
 - ways of representing 27–8
- safe crack growth period
 - multiple load path, damage tolerant structure 267, 268, 269, 270
 - single load path, damage tolerant structure 266
- ‘safe life’ concept 5
- safety factors, fatigue calculations and test results 18–19
- saw cut 186
- scarf joint 76, 77
 - as chordwise wing joint 303–4, 304, 305
- scatter factors
 - in fatigue tests and calculations 44–5
 - in repeat inspection interval calculations 277, 287
 - in threshold crack growth calculations 274, 355
- Schijve’s neutral line theory 66
 - secondary bending calculated using 66–7, 79, 382
- sea operations, gust data 214

- sealants
 - effect on stress concentration factor at joints 64
 - effect on stress concentration factor at open holes 56
- secondary bending
 - at bolt head 96, 380
 - calculation using Schijve's theory 66–7, 79, 382
 - and conservative stress calculation 65–6
 - fatigue life of joints affected by 65–7, 382
 - in repair doubler 382
- secondary damage (SD) 250
- secondary load path 250
- semi-elliptic surface flaw, SIF for 134–5
- semi-random loading 236, 237
- Service Bulletins 249
- service lives, WW2 aircraft 1
- shear lips 23, 24, 110, 189
- short crack behaviour 124–5
 - correction for 125–6, 298
- Sih's [stress intensity factor] method 147–8, 394
 - example calculation 149–51
- single load path, damage tolerant structure 265–7
 - examples 319, 332, 335, 348, 351
 - repeat inspection interval calculation 277–8
- single row lap joints 60, 385
- single shear joint 77
- size effect [on fatigue life] 21
 - lugs 87–8, 293
- size rating [in detectable crack calculations] 256
- skin
 - in stiffened panel
 - as PD item 325–31
 - as SD item 331–2
 - in wing skin joint
 - as PD item 307–11
 - as SD item 311–12
- skin crack stress intensity, rigid compared with flexible fasteners 174
- skin panel failure 196, 197, 199
 - load distribution after 198
- skin panel joints 53, 54, 77, 303, 306
- slip 15–16
 - critically resolved shear stress for 16
- small cracks at holes, SIFs for 136–45
- small flaws, calculations covering 273, 307, 308, 311, 322, 325, 333, 337, 344
- spanwise/chordwise wing joints, fatigue and damage tolerance analysis 303–13
- spar flange 335
 - attachment of wing skin to 336
 - heel and toe flaws in 338
 - as PD item 338–9
 - as SD item 336–8
- spar flange strap 313
- spar joints, fatigue and damage tolerance analysis 313–16
- spar web 335, 340–1
- spar web plate 313
- spars
 - fatigue and damage tolerance analysis 335–41
 - integrally machined 265–6
- special detailed inspection (SDET) 255
 - see also* NDT
- spectra *see* loading spectra
- spectrum of loading 26, 27
- spin-up of undercarriage leg 238
- spotfacing 372, 380
 - and oversizing 372–4
- spreadsheets
 - crack growth calculations 118
 - fatigue life calculations 45
 - limitations 45, 118
- spring back of undercarriage leg 238
- staggered rows, modelling of 177, 178
- standard loading spectra 240, 399
- static stress calculations, SSIs identified by 244–5
- statistics, and fatigue calculations 49–52
- step joints 77
- stiffened panel analysis 323–32
 - background data 271
 - configuration for example calculation 324
 - fuselage cut outs 343–4
 - open hole in wing 334
 - spar joints 315, 316
 - spars 337, 339
 - stringer run out 346
 - wing panels 310, 313
- stiffened panel analysis program 175, 179, 196
 - approach in absence of 394
- stiffened panels
 - compounding method applied to 175–6
 - cracks in 165–77
 - fatigue and damage tolerance analysis 323–32
 - geometry notation for 168
 - residual strength 196–9
 - SIFs for 167, 168–9, 169–70, 325
- stiffener
 - as crack-stopping element 265–6
 - ended 346–7

- stiffener (continued)
 - fuselage bulging effects suppressed by 159
 - as PD item 331–2
 - as SD item 325–30
- stiffener failure 168, 198, 199
- stiffening ratio 165–6
- stiffness ratio [stringer to panel], SIF affected by 168, 169
- stop drilling 358–61
 - marginal benefits 359, 360
- stop hole
 - cold working of 360–1
 - fatigue life 359
- strain life curve 48, 49
- strain life fatigue calculations 47–9
- strap joint
 - as chordwise wing joint 305, 306
 - as spanwise wing joint 306, 307
- stress amplitude 26
- stress concentration factors 19
 - for blend repairs 375, 376
 - at ellipse 103
 - in joints 54–6
 - for lugs 86, 87, 293–4
 - at open holes 20, 21, 54, 55, 103, 332–3
- stress concentrations
 - adjacent, effect on crack path 247, 248
 - fatigue crack initiation affected by 19–21, 245–6
 - superimposition of 245–6
 - visualisation of 21, 55, 56
- stress correction factors 33–4
- stress corrosion cracking 92, 371
- stress gradient
 - hole in tension 20
 - SIFs affected by 147–53, 394
- stress intensity 107
 - standard equation for calculating 111, 130, 133, 134, 136
- stress intensity factor (SIF) 130–80
 - application to analysis of lugs 144, 295–7
 - application to fatigue crack growth 114–17
 - calculation 273
 - for centre cracked panel 130–2, 193, 194
 - at crack tip 111
 - for cracks at holes 136–45, 394
 - for edge crack 132–4
 - effect of stress gradient 147–53
 - effect of thickness changes 153–4
 - integration of 369, 372, 395
 - for surface flaws 134–5
 - for through cracks at holes 146–7
- Stress Office, interface with NDT Department 264
- stress range 26, 29
- stress ratio 84, 377
- stress severity factor (SFF) 59–60
 - applications of approach 61
 - calculation examples 60–1, 78–9
- stress spectra 35–43
- stress stiffening effects, in fuselages 155, 156
- striations 22, 251
- stringer
 - factors affecting SIFs 168
 - joints 305, 306
 - in wing skin joint
 - as PD item 311–12
 - as SD item 307–11
- stringer run outs, fatigue and damage tolerance analysis 345–7
- structural adhesives, and knife edged countersinks 64–5, 317
- structural audit, and damage tolerance methods 274
- structurally significant items (SSIs) 242
 - blend repairs as 376, 377
 - identification of potential SSIs 243, 244
- structure modification point (SMP) 12
- summary sheet(s), compilation of 284
- summated increment method 118 & n
- superimposed stress concentrations 245–6
- superposition principle 139, 150, 166
- surface cracks, detection of 260
- surface flaws 7
 - SIFs for 134–5
- surface rating [in detectable crack calculations] 256–7
- Swedish FFA lug size correction factor 88
- Swift's fastener flexibility formula 71, 72
- taper in joints 76
- Taper-Lok fastener 84, 92, 384
- tapered plates, as series of stiffening elements 176–7
- taxi loading spectrum 36, 210, 227
- tear-down inspections 8, 95, 249, 250, 318
- tensile strength, fatigue strength affected by 31
- test data, SSIs identified using 249
- thin material, fracture surface 24
- thin sheet structures, joints in 77
- three row joint, load transfer through 72–5, 77–8, 78–9, 320, 385
- threshold
 - calculations 273–4, 291, 376
 - crack growth 114, 115, 123, 274, 355
 - fatigue 44, 274, 287
 - inspection 8, 9, 273–4, 302–3, 365, 374

- threshold (continued)
 - NDT detection 259–60, 261, 262, 263, 264, 356, 357, 365, 376
 - repairs 354, 355, 387
- threshold stress intensity 114, 115, 125
 - calculations 119, 120
- through cracks at holes, SIFs for 146–7
- toe flaw [in flange] 338
- toughness *see* critical fracture toughness; fracture toughness
- triaxial stress state, at crack tip 110, 112, 181
- truncation of fatigue test spectrum 4, 128, 129, 239
- TWIST standard loading spectrum 237, 240, 399
- two piece doubler in joints 76
- two row joint, load transfer through 77, 385

- ultimate tensile strength 272
- ultrasonic testing 263–4
- undercarriage loading 238–9
- up-gusts
 - cumulative frequencies for range of maximum stresses **221–3**
 - see also* down-gusts
- up-gusts/down-gusts ratio 215, 218

- variable amplitude fatigue loading cycle 26, 27
- Vickers-Armstrong Wellington bombers 1
- viewing rating [in detectable crack calculations] 256
- visual methods for detection of cracks 252–8
- Volkersen formula 99

- Walker equation 116
- weight distribution, in post-repair calculations 399–400
- weight function method 151
- weight reduction 245
- widespread fatigue damage (WFD) 10–12, 249
 - and repair doublers 393
 - see also* multiple element damage; multiple site damage
- window cut outs, fatigue and damage tolerance analysis 344–5
- window pan 344, 345
- wing, principal structural elements listed 242
- wing/empennage cut outs and holes, fatigue and damage tolerance analysis 332–4
- wing joints, fatigue and damage tolerance analysis 303–13
- wing skin 335
 - as PD item 336–8
 - as SD item 338–9
- wingbox rib 347
- Wöhler curve *see* SN curve
- worst case SN curve approach [for fatigue of joints] 81–2, 83
- Wright Flyer 1

- X-radiography 262–3, 390

- yield stress 110
- Young's modulus 272

- zero timing 355–7, 387